



PROGRIP

BONDING PRIMER TECHNICAL DATA SHEET

Progrip Bonding Primer for Floors & Driveways is a premium water-based bonding coat designed to prepare surfaces for long-lasting performance. Engineered to deliver excellent adhesion on previously coated floors, new concrete, and other challenging substrates, this primer prepares the surface for your finish coat to perform at its best. Ideal for both interior and exterior use, Progrip Primer creates a dependable foundation for Protread Floor Paint, enhancing durability and extending protection.

PRODUCT NAME

Progrip Bonding Primer

DESCRIPTION

A premium water-based bonding coat for floor coatings

SUGGESTED USES

Intended for use as a bonding primer on raw concrete, asphalt, and most previously sealed or coated substrates. Ideal for residential, commercial, and light industrial floor and driveway applications where maximum adhesion is needed.

COVERAGE

Theoretical coverage is 250–350 sq. ft. per gallon, depending on surface porosity and texture. Actual coverage will vary due to application method, surface profile, and material losses, and should be considered when estimating job requirements.

RECOMMENDED DRY TIME

Dries to the touch in 1–2 hours under direct sunlight. Recoat after 6–8 hours of direct sunlight.

SURFACE PREPARATION

Preparation for new or unpainted concrete: All surfaces must be clean, dry, and sound. Remove dirt, dust, oil, grease, wax, mildew, and curing compounds. Pressure wash (minimum 2500 PSI) and etch dense concrete as needed. New concrete must cure 60–90 days. Do not apply to damp surfaces, below 50°F (10°C), above 100°F (37°C), or when rain is expected.

Preparation for previously painted surfaces: Remove loose or peeling paint. Surfaces must be clean and free of contaminants. Protread Primer may be applied over most well-bonded coatings, but is not recommended over alkyds, epoxies, polyurethanes, or silicate sealers. Do not acid-etch painted surfaces.

MIXING

Apply as the product comes in the container.

APPLICATION

Apply one thorough, even coat. Apply with a brush, medium 3/8" nap roller, or airless spray.

COLORS	CLEAR
FINISH	PRIMER
VEHICLE TYPE	ACRYLIC EPOXY
SOLVENT TYPE	WATER
VOC	99 GM/L
FLASH POINT	NON-FLAMMABLE
SOLIDS BY WEIGHT	-
SOLIDS BY VOLUME	-
WEIGHT PER GALLON	-
RECOMMENDED WET FILM	-
VISCOSITY	-

PACKAGING

1 Gallons, 5 Gallons

SHELF LIFE

2 Years

LIMITATIONS

Do not apply to outdoor ramps/driveways with slopes steeper than 4.1 degrees. Do not apply to outdoor stairs or loading docks. Not for use on surfaces exposed to prolonged/standing water

SAFETY INFORMATION

Use with adequate ventilation. Do not ingest. Avoid prolonged contact with the skin. Wash immediately after use and before smoking and eating. Avoid breathing vapors and mist. In case of eye contact, flush eyes immediately with water and continue for at least 15 minutes and consult a physician. Close container after each use. Keep out of the reach of children. If you scrape, sand, or remove old paint, you may

PROGRIP BONDING PRIMER

release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800.424.LEAD or log on to www.epa.gov/lead.