



TRUESEAL 2K

TWO-COMPONENT URETHANE PAVER SEALER

TECHNICAL DATA SHEET

Trueseal 2K's two-component urethane technology provides all sealable surfaces with the highest level of durability and longevity currently available. This high enhancing, UV-resistant sealer produces a gloss finish and is non-yellowing and non-whitening. Surfaces can be pressure cleaned and sealed in the same day as Trueseal 2K can be applied over surface dry substrates to promote joint stabilization.

PRODUCT NAME

Trueseal 2K Two-Component Paver Sealer

DESCRIPTION

A two-component protective clear coat for concrete brick pavers, porous stone, brick and most cement surfaces.

SUGGESTED USES

For use on all porous concrete and cement surfaces, porous stone, pavers, brick, and decorative finishes. This sealer can also be used as concrete curing compound, concrete chatahoochee, and porous stamped concrete.

COVERAGE

Coverage averages depend on the porosity of the surface: Rolling - 300 sq. ft per gallon. Spraying - 400 sq. ft. per gallon.

RECOMMENDED DRY TIME

At 70 F and 50% relative humidity: Touch - 2 to 6 hours (depending on weather). Recoat - 3 to 6 hours. Surface will be tack free in 3 to 6 hours, ready for foot traffic in 12 to 24 hours and vehicle traffic in 72 hours. Dry times may vary depending on air temperature, wind, and humidity.

SURFACE PREPARATION

Preparation for new or unpainted concrete: Pavers must be clean, and free of any dirt, stains, and failed sealer. Testing of the surface is recommended to ensure desired results.

Preparation for previously painted surfaces:

MIXING

Trueseal 2K is a two-part product. Mix part A with part B before use. It is recommended to mix part A with part B using a paddle mixer attached to a power drill. If using a stirring stick, stir vigorously for a minimum of 2 minutes to ensure a complete induction. Part A is 4 parts and part B is 1 part, no measuring is necessary if activating the complete kit. Once the sealer is mixed, dilute the mixture once again with one part mixed sealer with one part water. Warning: If you use sealer undiluted, a slippery condition may occur.

APPLICATION

COLORS	CLEAR
FINISH	MATTE / SEMI-GLOSS / HIGH-GLOSS
VEHICLE TYPE	ACRYLIC URETHANE
SOLVENT TYPE	WATER
VOC	<50 GM/L
FLASH POINT	NON-FLAMMABLE
SOLIDS BY WEIGHT	-
SOLIDS BY VOLUME	-
WEIGHT PER GALLON	8.7 POUNDS (PART A) / 9.3 POUNDS (PART B)
RECOMMENDED WET FILM	-
VISCOSITY	-

Brush, Roller (min 3/8" nap), or spray. DO NOT APPLY excessive pressure on the roller, roll with light to medium pressure. Apply paver sealer evenly and try to minimize puddles or roller trails. Only one coat is required. Do not apply to areas where standing water is evident. Where there is a possibility of slipperiness. DO NOT APPLY THIS PRODUCT. If there has been a skid texture added to the base coat this product may perform properly but all precautions must be taken.

PACKAGING

1 Gallon Kit, 2 Gallon Kit, and 5 Gallon Kit

SHELF LIFE

2 Years

LIMITATIONS

Trueseal 2K must be stored in an air tight container. Once container is opened, pour out desired amount and immediately replace the lids. Any mixed material that is not used within 2 to 3 hours must be discarded

TRUESEAL 2K

TWO-COMPONENT URETHANE PAVER SEALER

and a new batch prepared. Do not attempt to save activated materials after 3 hours. Do not pour previously activated materials into a freshly activated batch. Keep out of reach of children. Do not take internally. Applicators should wear protective eyewear, gloves and NIOSH mask if spraying. If swallowed, contact a physician immediately. Limitation of Liability: Technical data is true and accurate to the date of issuance but not subject to change without notice. Our products conform to our quality standards, but no other warranty or guarantee is expressed or implied. Liability, if any, is limited to replacement of product or purchase price. Labor, cost of labor, equipment or consequential damages are excluded.

SAFETY INFORMATION

Use with adequate ventilation. Do not ingest. Avoid prolonged contact with the skin. Wash immediately after use and before smoking and eating. Avoid breathing vapors and mist. In case of eye contact, flush eyes immediately with water and continue for at least 15 minutes and consult a physician. Close container after each use. Keep out of the reach of children. If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage, especially in children. Pregnant women should also avoid exposure. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800.424.LEAD or log on to www.epa.gov/lead.